



classic 10-point touch screen ET range



dual OS ETD range with





# **BVS** ECOtouch

ost educational establishments are forever juggling their budgets to ensure their classrooms are equipped with the latest technology at the best possible price. If you are in this position, you have come to the right place. At BVS, our ethos is to bring you the highest quality products without compromising on features but at prices that are very affordable. Using professional grade LED panels, the BVS ECOtouch range has been developed to provide long term durability and performance for a typical learning environment. There is also a choice of screen sizes to suit every type of classroom.

ith all BVS ECOtouch screens, you can choose from a range of market leading software that will facilitate seamless integration and collaboration between students and teachers. The ability to use 10 points of touch is bound to engage and inspire your students. We've even included a useful Freeze Frame function for the teacher so you can work independently on your device while the class is occupied with a given task. The BVS ECOtouch screens are designed to give you outstanding quality. But if you have an issue, our market leading 7 year warranty will give you complete peace of mind.

# Choice of Software





# Year Warranty



The BVS 65" Screens are absolutely stunning! So much better than the old interactive whiteboards and projectors. Your prices are very keen and affordable. If any school is considering purchasing touch screens, your BVS ECOtouch 65" Screens tick all the boxes!

Penwortham Girls High School

# **BVS** ECOtouch

# the classic range designed for learning and presentation

# ET series



ring your lessons to life with the ET series screens boasting all the features you are likely to want, but at an amazingly low price.

Fascilitating 10 points of touch, anti-glare, freeze frame, full HD 1080P and an industry leading 7 Year warranty, the ET series is designed to put you in control.

Available in 3 popular sizes and 3 popular software options.

# the *classic* range

- 10 point touch
- Anti-glare toughened glass
- Built-in speaker
- Freeze frame
- Full HD 1080p wide screen
- Ultra quiet
- 7 year warranty



#### Hardware

#### 10-Point Infrared Touch Technology

Using the most durable and robust commercial touch technology available. Use anything such as your finger, or one of the styluses included, as your pointer.

#### Narrow Bezel

Connectivity

more permanent

connections such

out, RS-232, VGA,

HDMI, YPbPr, USB.

The rear of the

Stylish and sleek enclosure with rounded corners.



#### LED Backlight

eco-friendly LED backlight focusses on optimum brightness and contrast; causing no eye strain as you would get from projectors. The panel and backlight have a lifespan in excess of 80,000 hours.

#### Easy Access Ports Flexibility

Quickly and conveniently connect your own laptop to the screen using the front facing HDMI and Touch USB ports.

#### **Etched Glass**

Improves tactility for smooth touch gestures. The anti-glare nano coating also diffuses external light so that images and videos are much clearer.

Product Size W x H x D (mm)         1274.4 x 758.9 x 97.2         1512.4 x 902.4 x 92         1634 x 976 x 92.7           Display Area W x H (mm)         1290.6 x 680.4         1432.34 x 807.34         1553.4 x 875.6           Touch Technology         Inferred toll point touch         16.9           Brightness         500 cct/m²         16.9           Contriost Rotto         50000-1         178°           Verying Angle         178°         178°           Resolution         1920 x 1080         1820 x 1080           Uladimin (hours)         50000         1820 x 1080           Video         PAL/SECAM         50000           Video         PAL/SECAM         50000           Resolution (hours)         50000         1820 x 1080           Video         PAL/SECAM         50mm           Resolution (hours)         50mm         1820 x 1080           Resolution (hours)         2 x 15w         1820 x 1080           Resolution (interpolation)         3276 x 3276s         1820 x 1080           Touch Resolution (interpolation)         10 Point Touch - Android, Linux Windows 7/8/10         180 (much) x 1, USB (PO) x 1	BVS ECOtouch ET series	ET551 classic	ET651 classic	ET701 classic
Display Area W x H (mm)         1299 € x 680.4         143.2.4 x 807.34         1553.4 x 875.6           Touch Technology         Infrired 10 point fouch           Aspect Rollo         16.9           Brightness         500 cd/m2           Contrast Rollo         5000:1           Velving Angle         178*           Resolution         1920 x 1080           Uteline (house)         500000           Video         PAI/SECAM           Speciders         2 x 156V           Minimum Touch         \$5mm           Response Ilime         \$5ms           Positioning Accuracy         \$7ms           Touch Resolution (interpolation)         3276 x 32768           Interface         Uslimited           Touch Compatibility         10 Point Touch – Android, Linux, Windows 7/8/10           Touch Cingentibility         10 Point Touch – Android, Linux, Windows 7/8/10           Touch Linux         Unlimited           Inputs (side)         AV/Audiox 1, S/Video/Audiox 1, VSB (PO) x 1, VOX + I, HDMI x 1           Toutputs         AV/Audiox 1, S/Video/Audiox 1, VSB (PO) x 1, VOX + I, HDMI x 1           Power Supply         ACC110-240V (5014-2014)           Storage Flumidity         \$5ms           Storage Flumidity         \$5ms     <	Screen Size	55 inch	65 inch	70 inch
Touch Technology         Intrinced 10 point fouch           Aspect Retino         16-9           Righthass         500 cd/m2           Contrast Retilo         500001           Viewing Angle         178°           Resolution         1920 x 1080           Lifetime (hours)         500000           Video         PAL/SECAM           Species         2 x 15W           Minimum Touch         2 5mm           Response Time         5 5ms           Postloning Accuracy         2 mm           Touch Resolution (interpolation)         3286 x 32788           Interface         188           Touch Compatibility         10 Point Touch - Android, Linux, Windows 7/8/10           Touch Times         UBS (rouch) x 1, USB (rol x) x 1, VSB (rol x) x 1, HDM1 x 1           Inputs (ried)         AV/Audio x 1, VSB (rol x) x 1, VSB (rol x 1, HDM1 x 1           Inputs (ried)         AV/Audio x 1, VSB (rol x) x 1, VSB (rol x 1, HDM1 x 1           Inputs (ried)         AV/Audio x 1, VSB (rol x 1, HDM1 x 1           Inputs (ried)         AV/Audio x 1, VSB (rol x 1, HDM1 x 1           Outputs         AV/Audio x 1, VSB (rol x 1, HDM1 x 1           Power Sourpilon (slondby)         S 5m           Storage Famewardure         6 °C <t< td=""><td>Product Size W x H x D (mm)</td><td>1274.4 x 758.9 x 97.2</td><td>1512.4 x 902.4 x 92</td><td>1634 x 976 x 92.7</td></t<>	Product Size W x H x D (mm)	1274.4 x 758.9 x 97.2	1512.4 x 902.4 x 92	1634 x 976 x 92.7
Aspect Ratio         16-9           Binghness         500 cd/m2           Controst Ratio         5000-1           Viewing Angle         178°           Resolution         1920 x 1080           Lifetime (hours)         500000           Video         PAL/SECAM           Speckers         2 x 15W           Minimum Touch         5 fmm           Response Time         5 fms           Positioning Accuracy         5 fms           Positioning Accuracy         2 mm           Touch Compatibility         10 Point Touch - Android, Linux, Windows 7/8/10           Touch Compatibility         10 Point Touch - Android, Linux, Windows 7/8/10           Touch Times         Unlimited           Inputs (steam)         4 X/Audio x 1, SV/Ade/Audio x 1, VGA x 1, HDM x 1           Inputs (steam)         AV/Audio x 1, SV/Ade/Audio x 1, VGA x 1, HDM x 1           Inputs (steam)         AV/Audio x 1, SV/Ade/Audio x 1, VGA x 1, HDM Inteled           Inputs (steam)         AV/Audio x 1, SV/Ade/Audio x 1, Coaxiel Digital Audio x 1           Outputs         AV/Audio x 1, SV/Ade/Audio x 1, Coaxiel Digital Audio x 1           Power Supply         ACTIO-240V (50Hz-50Hz)           Storage Famperature         5 °C           Working Humidity         S a Coaxiel (st	Display Area W x H (mm)	1209.6 x 680.4	1432.34 x 807.34	1553.4 x 875.6
Brightness         500 cd/m2           Contrast Ratio         5000:1           Viewing Angle         178°           Resolution         1920 x 1080           Lifetime (hours)         500000           Video         PAL/SECAM           Speakers         2 x 15W           Minimum Touch         2 5 mm           Response Time         ≤ 5 ms           Positioning Accuracy         5 5 ms           Positioning Accuracy         3278 x 32768           Interface         USB           Touch Resolution (Interpolation)         3278 x 32768           Interface         USB           Touch Compatibility         10 Point Touch – Android, Linux, Windows 7/8/10           Touch Times         Unlimited           Inputs (right)         4 AV/Audio x 1, VGA/Audio x 1, VGA/Audio x 1, VGA/X 1, HDMIx 1           Inputs (side)         AV/Audio x 1, SV/Ideo/Audio x 1, VGA/Audio x 1, VGA/X 1, HDMIx 1           Inputs (side)         AV/Audio x 1, SV/Ideo/Audio x 1, VGA/Audio x 1, VG	Touch Technology	Infrared 10 point touch		
Contrast Ratio         5000:1           Viewing Angle         178°           Resolution         1920 x 1080           Lifetime (hours)         500000           Video         PAL/\$ECAM           Speckers         2 x 15W           Minimum Touch         5 5mm           Response Time         ≤ 5mm           Positioning Accuracy         ± 2mm           Touch Resolution (Interpolation)         32768 x 32768           Interface         USB           Touch Compatibility         109 Point Touch – Android, Linux, Windows 7/8/10           Touch Immes         Uslimited           Inputs (fard)         45 Ke (Ouch) x 1, VSB (PC) x 1, VSA x 1, HDMIx 1           Inputs (side)         AV/Audio x 1, S-Video/Audio x 1, VPbPr/VCbCr, HDMI. Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, VSA/Audio x 1,	Aspect Ratio	16:9		
Viewing Angle         178°           Resolution         1920 x 1080           Lifelime (hours)         500000           Video         AL/SECAM           Speakers         2 x 15W           Minimum Touch         ≤ 5mm           Response Time         ≤ 5ms           Positioning Accuracy         ≤ 5ms           Touch Resolution (Interpolation)         32768 x 32768 x 32768           Interface         USB           Touch Compatibility         10 Point Touch - Android, Linux, Windows 7/8/10           Touch Times         USB (rouch) x 1, USB (rouch) x 1, USB (PC) x 1, VGA x 1, HDMI x 1           Inputs (front)         USB (rouch) x 1, USB (PC) x 1, VGA x 1, HDMI x 1           Inputs (side)         AV/Audio x 1, S-Video/Audio x 1, VPSP/PYCCCC, HDMI, Multi-Media USB x 1, Touch USB (type B) x 1           Outputs         AV/Audio x 1, S-Video/Audio x 1, VPSP/PYCCCC, HDMI, Multi-Media USB x 1, Touch USB (type B) x 1           Power Supply         AC110-240V (50Hz-6Hz)           Power Consumption (standby)         \$ C           Storage Temperature         \$ C           Working Humidity         \$ C           Storage Temperature         \$ C           Working Humidity         \$ C           Storage Temperature         \$ C           Working Humidity<	Brightness	500 cd/m2		
Resolution         1920 x 1080           Lifetime (hours)         50000           Video         PAL/SECAM           Speakers         2 x 15W           Minimum Touch         ≥ 5mm           Response Time         ≤ 5ms           Positioning Accuracy         ± 2mm           Touch Resolution (Interpolation)         32768 x 3278           Interface         USB           Touch Compatibility         10 Point Touch – Android, Linux, Windows 7/8/10           Touch Times         Unlimited           Inputs (side)         AV/Audio x 1, 3-Video/Audio x 1, VSB (Po) x 1, VSB x N 1, TOUR, Multi-Mexical USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, 3-Video/Audio x 1, VSBA/Audio x 1, YYPP/Y/VSDcr. HDMI, Multi-Mexical USB x 1, Touch USB (Type B) x 1           Power Supply         AV/Audio x 1, 3-Video/Audio x 1, VSBA/Audio x 1, YYPP/Y/VSDcr. HDMI, Multi-Mexical USB x 1, Touch USB (Type B) x 1           Power Consumption (standby)         AV/Audio x 1, 3-Video/Audio x 1, VSBA/Audio x 1, YYPP/Y/VSDcr. HDMI, Multi-Mexical USB x 1, Touch USB (Type B) x 1           Storage Temperature         5.5%           Storage Temperature         5.5%           Storage Temperature         5.5%           Working Humidity         10%           Storage Temperature         5.5%           VESA Holes W H M D (M)	Contrast Ratio	5000:1		
Lifetime (hours)         50000           Video         PAL/SECAM           Speakers         2 x 15W           Minimum Touch         ≤ 5mm           Response Time         ≤ 5ms           Positioning Accuracy         ± 2 mm           Touch Resolution (interpolation)         32568 x 32768           Touch Compatibility         10 Point Touch – Android, Linux, Windows 7/8/10           Touch Times         Uslimited           Inputs (front)         4 X/Audio x 1, SVI deo/Audio x 1, VSA/Audio x 1, VSA	Viewing Angle	178°		
Video         PAL/SECAM           Speakers         2 x 15W           Minimum Touch         ≥ 5mm           Response Time         ≤ 5ms           Positioning Accuracy         ± 2mm           Touch Resolution (Interpolation)         32768 x 32768           Interface         USB           Touch Compatibility         10 Point Touch – Android, Linux, Windows 7/8/10           Touch Times         Unlimited           Inputs (front)         USB (fouch) x 1, USB (PC) x 1, VGA x 1, HDMI x 1           Inputs (side)         AV/Audio x 1, S-Video/Audio x 1, VBA/PC/bCr, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, S-Video/Audio x 1, VBA/PC/bCr, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, Coaxial Digital Audio x 1           Power Consumption (standby)         AV/Audio x 1, Coaxial Digital Audio x 1           Power Consumption (standby)         AV/Audio x 1, Coaxial Digital Audio x 1           Storage Temperature         5°C           Working Humidity         10%           Storage Temperature         5°C           Working Humidity         10%           Storage Fundantie         Femoter Control, AC power cable, USB cable, HDMI cable           Power Consumption (W)         ≤ 120W         ≤ 120W	Resolution	1920 x 1080		
Speakers         2 x 15W           Minimum Touch         ≥ 5mm           Response Time         ≤ 5ms           Positioning Accuracy         ± 2mm           Touch Resolution (Interpolation)         32768 x 3276	Lifetime (hours)	50000		
Minimum Touch         ≥ 5mm           Response Time         ≤ 5ms           Positioning Accuracy         ± 2mm           Touch Resolution (Inferpolation)         32768 x 32768           Interface         USB           Touch Compatibility         10 Point Touch – Android, Linux, Windows 7/8/10           Touch Times         Unlimited           Inputs (front)         USB (touch) x 1, USB (PC) x 1, VGA x 1, HDMI x 1           Inputs (side)         AV/Audio x 1, S-Video/Audio x 1, VGA/Audio x 1, YPPP/YCDC, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, S-Video/Audio x 1, VGA/Audio x 1, YPPP/YCDC, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, S-Video/Audio x 1, VGA/Audio x 1, YPPP/YCDC, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, S-Video/Audio x 1, VGA/Audio x 1, YPPP/YCDC, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, S-Video/Audio x 1, YPPP/YCDC, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, S-Video/Audio x 1, YPPP/YCDC, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, S-Video/Audio x 1, YPPP/YCDC, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, S-Video/Audio x 1, YPPP/YCDC, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs <td>Video</td> <td colspan="3">PAL/SECAM</td>	Video	PAL/SECAM		
Response Time         ≤ 5ms           Positioning Accuracy         ± 2mm           Touch Resolution (Interpolation)         32768 x 32768 x 32768           Interface         USB           Touch Compatibility         10 Point Touch - Android, Linux, Windows 7/8/10           Touch Times         Unlimited           Inputs (front)         USB (touch) x 1, USB (PC) x 1, VGA x 1, HDM1 x 1           Inputs (side)         AV/Audio x 1, S-Video/Audio x 1, VGA/Audio x 1, VGA/PDF/YCEOC, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, Coaxiel Digital Audio x 1           Power Supply         AC110-240V (50Hz-60Hz)           Power Consumption (standby)         S °C           Working Humidity         5 °C           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Power Consumption (W)         5 180 x 120 x 31<	Speakers	2 x 15W		
Positioning Accuracy         ± 2mm           Touch Resolution (Interpolation)         32768 x 32768           Interface         USB           Touch Compatibility         10 Point Touch - Android, Linux, Windows 7/8/10           Touch Times         Unlimited           Inputs (front)         USB (touch) x 1, USB (PC) x 1, VGA x 1, HDMI x 1           Inputs (side)         AV/Audio x 1, S-Video/Audio x 1, VS-A/Audio x 1, VS-PbPr/YCbCr, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, S-Video/Audio x 1, S-Video/Audio x 1, Coaxid Digital Audio x 1           Power Supply         AC110-240V (50Hz-60Hz)           Power Consumption (standby)         ≤ 0.5W           Storage Temperature         5 °C           Working Humidity         10%           Storage Humidity         35%           Accessories         Remote control, AC power cable, USB cable, HDMI cable           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg)         45         67         75	Minimum Touch	≥ 5mm		
Touch Resolution (Interpolation)         32768 x 32768           Interface         USB           Touch Compatibility         10 Point Touch - Android, Linux, Windows 7/8/10           Touch Times         Unlimited           Inputs (front)         USB (touch) x 1, USB (PC) x 1, VGA x 1, HDMI x 1           Inputs (side)         AV/Audio x 1, PPbPr/YCBC, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, Coaxial Digital Audio x 1           Power Supply         AC110-240V (50Hz-40Hz)           Power Consumption (standby)         S°C           Working Humidity         10%           Storage Temperature         5°C           Working Humidity         10%           Storage Humidity         35%           Accessories         Remote control, AC power cable, USB cable, HDMI cable           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg) <th< td=""><td>Response Time</td><td colspan="3">≤ 5ms</td></th<>	Response Time	≤ 5ms		
Interface         USB           Touch Compatibility         10 Point Touch - Android, Linux, Windows 7/8/10           Touch Times         Unlimited           Inputs (front)         USB (touch) x 1, USB (PC) x 1, VGA x 1, HDMI x 1           Inputs (side)         AV/Audio x 1, S-Video/Audio x 1, VGA/Audio x 1, YPbPr/VCbCr, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, Cooxial Digital Audio x 1           Power Supply         AC110-240V (50Hz-60Hz)           Power Consumption (standby)         S C           Working Humidity         10%           Storage Temperature         5°C           Working Humidity         10%           Storage Humidity         35%           Accessories         Remote control, AC power cable, USB cable, HDMI cable           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg)         45 <td>Positioning Accuracy</td> <td colspan="3">± 2mm</td>	Positioning Accuracy	± 2mm		
Touch Compatibility         10 Point Touch - Android, Linux, Windows 7/8/10           Touch Times         Unlimited           Inputs (front)         USB (fouch) x 1, USB (PC) x 1, VGA x 1, HDMI x 1           Inputs (side)         AV/Audio x 1, S-Video/Audio x 1, VGA/Audio x 1, VPbPr/YCbCr, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, Coaxial Digital Audio x 1           Power Supply         AC110-240V (50Hz-60Hz)           Power Consumption (standby)         ≤ 0.5W           Storage Temperature         5°C           Working Humidity         10%           Storage Humidity         35%           Accessories         Remote control, AC power cable, USB cable, HDMI cable           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg)         45         67         75	Touch Resolution (Interpolation)	32768 x 32768		
Touch Times         Unlimited           Inputs (front)         USB (fouch) x 1, USB (PC) x 1, VGA x 1, HDMI x 1           Inputs (side)         AV/Audio x 1, YPbPr/YCbCr, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, Coaxial Digital Audio x 1           Power Supply         AC110-240V (50Hz-60Hz)           Power Consumption (standby)         AC110-240V (50Hz-60Hz)           Storage Temperature         5°C           Working Humidity         10%           Storage Humidity         35%           Accessories         Remote control, AC power cable, USB cable, HDMI cable           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg)         45	Interface	USB		
Inputs (front)         USB (touch) x 1, USB (PC) x 1, VGA x 1, HDMI x 1           Inputs (side)         AV/Audio x 1, VGA/Audio x 1, VGA/Audio x 1, VGA/Audio x 1, Coaxial Digital Audio x 1           Outputs         AV/Audio x 1, Coaxial Digital Audio x 1           Power Supply         AC110-240V (50Hz-60Hz)           Power Consumption (standby)         AC110-240V (50Hz-60Hz)           Storage Temperature         5°C           Working Humidity         10%           Storage Humidity         35%           Accessories         Remote control, AC power cable, USB cable, HDMI cable           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg)         45	Touch Compatibility	10 Point Touch – Android, Linux, Windows 7/8/10		
Inputs (side)         AV/Audio x 1, S-Video/Audio x 1, VGA/Audio x 1, YPbPr/YCbCr, HDMI, Multi+Media USB x 1, Touch USB (Type B) x 1           Outputs         AV/Audio x 1, Coaxial Digital Audio x 1           Power Supply         AC110-240V (50Hz-60Hz)           Power Consumption (standby)         ≤ 0.5W           Storage Temperature         5°C           Working Humidity         10%           Storage Humidity         35%           Accessories         Remote control, AC power cable, USB cable, HDMI cable           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg)         45         67         75	Touch Times	Unlimited		
Outputs         AV/Audio x 1, Coaxial Digital Audio x 1           Power Supply         AC110-240V (50Hz-60Hz)           Power Consumption (standby)         ≤ 0.5W           Storage Temperature         5°C           Working Humidity         10%           Storage Humidity         35%           Accessories         Remote control, AC power cable, USB cable, HDMI cable           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg)         45         67         75	Inputs (front)	USB (touch) $\times$ 1, USB (PC) $\times$ 1, VGA $\times$ 1, HDMI $\times$ 1		
Power Supply         AC110-240V (50Hz-60Hz)           Power Consumption (standby)         ≤ 0.5W           Storage Temperature         5°C           Working Humidity         10%           Storage Humidity         35%           Accessories         Remote control, AC power cable, USB cable, HDML cable           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg)         45         67         75	Inputs (side)	AV/Audio x 1, S-Video/Audio x 1, VGA/Audio x 1, YPbPr/YCbCr, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1		
Power Consumption (standby)         ≤ 0.5W           Storage Temperature         5°C           Working Humidity         10%           Storage Humidity         35%           Accessories         Remote control, AC power cable, USB cable, HDMI cable           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg)         45         67         75	Outputs	AV/Audio x 1, Coaxial Digital Audio x 1		
Storage Temperature       5°C         Working Humidity       10%         Storage Humidity       35%         Accessories       Remote control, AC power cable, USB cable, HDMI cable         Power Consumption (W)       ≤ 120W       ≤ 180W       ≤ 230W         VESA Holes W x H (mm)       400 x 400       600 x 400       400 x 500         Package Size W x H x D (mm)       1450 x 951 x 256       1735 x 1165 x 315       1834 x 1220 x 315         Net Weight (kg)       45       67       75	Power Supply	AC110-240V (50Hz-60Hz)		
Working Humidity $10\%$ Storage Humidity $35\%$ Accessories $ \begin{array}{ccccccccccccccccccccccccccccccccccc$	Power Consumption (standby)	≤ 0.5W		
Storage Humidity         35%           Accessories         Remote control, AC power cable, USB cable, HDMI cable           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg)         45         67         75	Storage Temperature	5°C		
Accessories         Remote control, AC power cable, USB cable, HDMI cable           Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg)         45         67         75	Working Humidity	10%		
Power Consumption (W)         ≤ 120W         ≤ 180W         ≤ 230W           VESA Holes W x H (mm)         400 x 400         600 x 400         400 x 500           Package Size W x H x D (mm)         1450 x 951 x 256         1735 x 1165 x 315         1834 x 1220 x 315           Net Weight (kg)         45         67         75	Storage Humidity	35%		
VESA Holes W x H (mm)       400 x 400       600 x 400       400 x 500         Package Size W x H x D (mm)       1450 x 951 x 256       1735 x 1165 x 315       1834 x 1220 x 315         Net Weight (kg)       45       67       75	Accessories	Remote control, AC power cable, USB cable, HDMI cable		
Package Size W x H x D (mm)       1450 x 951 x 256       1735 x 1165 x 315       1834 x 1220 x 315         Net Weight (kg)       45       67       75	Power Consumption (W)	≤ 120W	≤ 180W	≤ 230W
Net Weight (kg) 45 67 75	VESA Holes W x H (mm)	400 x 400	600 x 400	400 x 500
	Package Size W x H x D (mm)	1450 x 951 x 256	1735 x 1165 x 315	1834 x 1220 x 315
Gross Weight (kg) 55 77 85	Net Weight (kg)	45	67	75
	Gross Weight (kg)	55	77	85

TM

We are really impressed with the robustness and build quality of the screen, the picture clarity is outstanding on such a large screen and the touch sensitivity is pin point perfect. We have been really pleased with the service received and the quality of the product. We would have no hesitation in recommending the BVS ECOtouch screens. Thank you and best wishes.

Mark Kelland, Commercial Manager, Dragon2000 Ltd

TM

From my initial contact to the subsequent order, delivery and installation of our first Touchscreen, we have been delighted with the service, product knowledge and cost of the equipment.

The skilled engineers who installed the touchscreens were extremely polite, worked quickly and efficiently. We have since gone onto to have seven more BVS ECOtouch touchscreens installed and each time, have been extremely delighted with the product.

Judith Buckley, Holymead Pimary School

# **BVS** ECOtouch

## the **smart** option designed for learning and presentation

# ETD series

aking your experience to a new level, the all-in-one ETD series boasts a unique combination of Android and Windows 10 Pro Dual Operating systems.

Combining this with integrated wi-fi, integrated microphone & camera and wireless mirroring, you have a touch screen that is hard to beat on both features and price. All this on top of the excellent features of the ET series.

dual OS ETD range with









- 10 point touch
- Anti-glare toughened glass
- Built-in speaker
- Freeze frame
- Full HD 1080p wide screen
- Ultra quiet
- 7 year warranty

# plus

- Integrated Android + Windows 10 dual OS
- Integrated 64gb storage
- Built-in PC
- Integrated Wi-Fi
- Integrated camera & microphone
- Wireless mirroring






## **Dual OS**

Experience the most versatile Interactive Touch Display on the market. With both Android and Windows operating systems installed on the integrated PC it cannot be beaten on flexibility. Seamlessly switch your operating system with just the push of a button; this screen has it all in one convenient package. With the huge number of apps available for Android and the world's most popular operating system in Windows the display is ready to take your meetings and lessons to the next level.



## Wireless Mirroring

Mirror what is on your Windows, Android or Apple device without the need for messy cables with the wireless mirroring feature this display offers. Great for presenting and sharing content during meetings it is done using your devices native streaming platform – Screen Mirroring for Android, Miracast for Windows and AirPlay for Apple. Mirroring the display from your mobile, tablet or laptop has never been easier.



## Infrared Touch

The Interactive Touch Displays use Infrared touch which is the most robust and durable interactive technology available. Designed for use in commercial applications, infrared touch technology works by embedding LED lights and sensors into the bezel of a monitor above the etched glass. These LED's beam a signal across to the corresponding sensor on the other side forming an invisible grid. When the grid is broken by a finger, or other solid object, the sensors can detect the touch point. Infrared touch screens are by far the most cost effective solution on the market.



# Integrated Camera / Microphone

Capture important meetings and lessons in real time with the front facing 5 megapixel camera that supports 1080p video recording and the directional microphone that has a range up to 45m2. The display can also capture and save what is on the display at any given time. These recordings and screenshots can then be archived and shared afterwards.

#### Hardware

#### Camera

The screen has an integrated 5 megapixel camera for teleconferencing and recording important meetings and lessons.

#### 10-Point Infrared Touch Technology

Using the most durable and robust commercial touch technology available. Use anything such as your finger, or one of the styluses included, as your pointer.

#### Narrow Bezel

Stylish and sleek enclosure with rounded corners.

#### Built-in PC

Featuring an integrated PC with 2GB RAM and 64GB ROM, meaning no additional external PC is required.

#### Connectivity

The rear of the screen features AV inputs that allow for more permanent connections such as AV, Audio in and out, RS-232, VGA, HDMI, YPbPr, USB.



#### Dual OS

The integrated PC has both Windows and Android operating systems installed. Seamlessly switch between the two for the most versatile touch screen solution on the market.





#### LED Backlight

The long lasting eco-friendly LED backlight focusses on optimum brightness and contrast; causing no eye strain as you would get from projectors. The panel and backlight have a lifespan in excess of 80,000 hours.

#### Easy Access Ports and Controls

Quickly and conveniently connect your own laptop to the screen using the front facing HDMI and Touch USB ports. There are also USB ports connected to the internal PC for easy access.

#### Microphone

The screen has an integrated microphone with a range of 45m2 for teleconferencing and recording important meetings and lessons.

#### **Etched Glass**

Improves tactility for smooth touch gestures. The anti-glare nano coating also diffuses external light so that images and videos are much clearer.

#### Integrated Software



#### Wireless Mirroring

Connect to the Touch Screen with any smartphone, tablet, laptop or PC without the need for any wires or any additional hardware. Using the Eshare app you can mirror the Touch Screen's display onto your device, and even take control of it, from anywhere on the same Wi-Fi network. Wireless mirroring is from your device to the Touch Screen is also possible without the need for any additional hardware.

#### File Sharing

Once your device and the Touch Screen are wirelessly connected you can quickly and easily share content to and from your device. Use the Eshare app to show videos, image and audio files stored on your smartphone, tablet, laptop or PC. You can also share files from the Touch Screen to your device using various methods such as email or scanning a QR code. Files can easily flow between the Touch Screen and your devices.


Unlimited

Connections

There is no limit

#### Flexible Working Tools

Personalise your experience by changing the background colour of the display, as well as the colour, thickness and opacity of the lines with your drawing tools.



#### **Annotations**

Make notes on your existing documents, screenshots and even webpages, Expand and innovate your content with ideas and concepts.

#### Whiteboard

Replaces the traditional marker board in meeting rooms and classrooms, Annotate, draw and create meeting magic with the

#### Web Browser-

Surf the web with the integrated internet browser.



#### Snipping tool

Crop segments of the display to shift focus to more important sections of documents. screenshots or webpages.

The marauee text tool is fun and innovative way to make important messages stand out, such as setting up welcome messages for your visitors.



















BVS ECOtouch ETD series	ETD651 dual OS	70" ETD701 <i>dual O\$</i>	
Screen Size	65 inch	70 inch	
Product Size W x H x D (mm)	1503.6 x 901.58 x 84.88	1617.8 x 961.9 x 88.5	
Display Area W x H (mm)	1431 x 807	1541 x 858	
Touch Technology	Infrared 10 point touch		
Aspect Ratio	16:9		
Contrast Ratio	4000:1		
Resolution	1920 x 1080		
Lifetime (hours)	80000		
Colour	16.7M		
Glass Hardness	7H minimum		
Response Time	≤ 4ms		
Touch Point Accuracy	± 1.5mm		
Touch Compatibility	10 Point Touch - Android, Linux, Windows 7/8/10		
Camera	5 Megapixel CMOS Sensor, Supports 1080p Video Recording		
Microphone	Directional Microphone with Range up to 45m <sup>2</sup>		
Speaker Output	2 x 15W (Front)		
Operating System	Android 4.4.4 KitKat Windows 10 Pro (licence purchased separately)		
Processor	Intel® Atom (Quad-core) Z3735F (2M Cache, up to 1.83 GHz)		
RAM	2GB (DDR3L-RS 1333)		
Instruction Set	64-bit		
Internal Memory	64GB		
Interface	USB 2 x USB 2.0, LAN,10/100M Ethernet, Wi-Fi, 802.11b/g/n		
Inputs (front)	Touch USB (touch) x 1, USB (PC) x 3, HDMI x 1		
Inputs (side)	AV/Audio, RS232 Port, VGA/Audio, HDMI, USB, Touch USB		
Outputs	VGA & Headphone Jack		
Power Supply	AC110-240V (50Hz-60Hz)		
Power Consumption (W)	≤ 180W	≤ 230W	
Accessories	Remote Control, User Manual, Power Cable, USB to USB Cable, Wi-Fi Aerial		
VESA Holes W x H (mm)	600 x 400	500 x 400	
Package Size W x H x D (mm)	1735 x 1165 x 315	1834 x 1220 x 315	
Net Weight (kg)	67	75	
Gross Weight (kg)	77	85	

I just wanted to say I really appreciate the excellent and professional service I received. This was our first order and you provided me with excellent product knowledge and the relevant guidance to help us purchase a number of interactive screens. We are extremely pleased with the quality of the product and service, many thanks

Eden Therapeutic Education Ltd

I was very impressed with your knowledge and understanding of what's needed in education. Money is tight within education and your prices are very competitive. We initially ordered the one recommended BVS ECOtouch solution, which was successfully installed by your excellent installation team. I've just ordered 5 more and will be ordering more in the very near future.

Corpus Christi RC High School

The reseller provided us with an excellent product at an excellent price, but what was most exceptional was the after-sales service. When we had a problem with our device, a replacement was brought out to us the very next day. This meant our teachers and students were able to continue teaching and learning with no interruption...

The Ridge Primary School

I have been very pleased with the products and level of service from the reseller. The 7 BVS ET651 65" touch screens they have provided are high quality and very good value for money, and the customer care has been excellent. I would strongly recommend BVS touch screens to any school looking to implement this technology.

Beaupre Primary School

I ordered a BVS ECOtouch 65" Interactive Touch Screen and Fixed Height Mobile Trolley on behalf of a local charity. We were very pleased with the service, price, and product that we received. So pleased in fact, that we are looking to purchase another package to the same specification.

Ealing Mencap

# www.bvstouchscreens.com